

FLAME RETARDANT

PRODUCT DATA SHEET



Product Code 8*-AD-FR **Description** FLAME RETARDANT FOR SOLVENT BASED INKS

8*-AD-FR Flame Retardant can be added to solvent-based and UV inks to impart flame-retardant properties to the ink.

For direct printing it must be used in conjunction with a flame retardant fabric.
For transfers it must be used with a flame retardant adhesive and applied to a flame-retardant fabric

Addition 15 – 25% - stir well before use

Testing must be carried out by Customers to ensure suitability prior to any production runs being carried out.

Suitable Ink systems	Transcreen DE2 86-OK-	Screenflec DE2-RM 86-RM-	Screenfab Slow 86-10-	Screenfab DE2 86-82-
				
	Screenfab DE5 85-01-	Screenflec DE5-RM 85-RM-	Screenfab DE5 85-OP-	
				

Appearance Clear, colourless liquid.

Odour Mild

Supplied Ready to use - Ex stock - Pack sizes 1kg and 5kg.

Shelf Life 12 months in unopened containers

Storage Store in closed containers in a cool environment between 5°C (41°F) and 25°C (77°F), out of direct sunlight & away from heat sources.

Notes The information provided is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You should satisfy yourself before applying any of the information contained herein to your particular circumstances. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted by Perfectos Printing Ink

PERFECTOS PRINTING INKS CO LTD
BOTTESFORD
NOTTINGHAM NG13 0EL
ENGLAND

TELEPHONE
FAX
E-MAIL
WEB SITE

+44 1949 842179
+44 1949 843493
info@perfectos.co.uk
www.perfectos.co.uk

All information is given in good faith but without warranty expressed or implied. All products are supplied in accordance with our Terms & Conditions of Trading